

ADDITIONAL INSTALLED EQUIPMENT LIST

INSTALLED ADDITIONAL EQUIPMENT LIST (revised 1/16/08)

2008
Condition Rating

Description	Very Good	Average	Minimum
Radio Telemetry			
Unit (RTU) (Master)	5,382	3,887	897
(Large)	6,439	4,651	1,073
(Small)	4,325	3,124	721
Cathodic Protection Unit			
with Rectifier	2,577	1,862	430
with Solar Panels	6,343	4,581	1,057
Gas Meter Run	7,076	5,110	1,179
LACT Unit	23,134	16,708	3,856
Gas Booster Line			
Compressor (15-30 HP)	37,678	27,211	6,280
In-Line Heater	6,400	4,622	1,067
Triplex Water Injection Pump			
75 HP Electric Motor	29,574	21,360	4,929
Chemical Pump	1,067	771	178
Recycle Pump	1,311	946	219
Chemical Tanks (55-125 Gal.)	197	142	33
Fuel/Chemical Tanks (500 Gal.)	655	474	109
Pit Tanks	699	568	131
Water Flow Lines (per foot)	6.86	4.95	1.15
Separators:			
48" x 12'	14,771	10,669	2,462
30" x 10'	11,398	8,232	1,900
Free Water Knockouts			
30" x 10'	3,342	2,414	557
4 x 10	5,242	3,786	874
6 x 10	8,820	6,370	1,470
8 x 10	11,729	8,471	1,955
4 x 15	8,191	5,916	1,365
6 x 15	12,288	8,875	2,048
Dehydrator			
Average of All Sizes	26,011	18,786	4,335
Wellheads			
Flanged Wellhead (Total Value)*	18,810	13,585	3,135
Threaded Wellhead (Total Value)*	6,714	4,849	1,119
Flanged Wellhead (Differential)**	12,097	8,737	2,017
Flanged/Threaded Combo (Differential)**	9,406	6,793	1,565

2008 – Additional Installed Equipment

	Condition Rating		
	Very Good	Average	Minimum
Vapor Recovery System	10,921	7,887	1,820
Vapor Flare System (Enclosed Stack)	10,204	7,369	1,701
Sound Panels (Galvanized Steel)			
Wall & Roof Panels/Sq.Ft. (Padded)	3.88	2.81	0.65
Scrubber	437	315	73
 <u>Waste Oil Recycling Operations Only:</u>			
Tank (1) 300 BBL	9,426	6,808	1,571
Separator 30" x 10' Vertical	6,185	4,466	1,031
Separator 24" x 10' Horizontal	12,709	9,179	2,118

***For use only with wells having dual wellheads on same wellbore.**

****For use only in Basins where Threaded Wellheads are typical (see Valuation Procedures)**